



FULLY AUTOMATIC FILLING & SEALING MACHINE

MODEL NB 070 A-BIS

FOR LIQUID

MODEL NB 070 B-BIS

FOR PASTE



**OUTPUT:
60 PCS/MIN**

A fully automatic machine for filling and sealing cups with Alu-foil lids with an extremely broad range of products and with a large capacity up to 500 cc (20 Oz).

The entire process is carried out automatically, with most operations conducted pneumatically under electronic control from a waterproof control panel

FULLY AUTOMATIC FILLING & SEALING MACHINE

MODEL NB 070-BIS

SPECIAL FEATURES

- EXCEPTIONAL VERSALITY OF THE MACHINE CAPABLE OF FILLING A BROAD RANGE OF PRODUCTS: FROM THIN VISCOUS LIQUIDS TO PASTES
- OPTION: TWO FILLING OPERATIONS CAN BE PERFORMED IN THE SAME CUP BEFORE SEALING (EX: YOGURT TOPPED WITH GRANOLA OR PUDDING TOPPED WITH WHIPPED CREAM)
- ALL PARTS IN CONTACT WITH THE FILLED PRODUCT ARE MADE OF STAINLESS STEEL. THE MACHINE ITSELF IS MADE OF STAINLESS STEEL, ANODIZED ALUMINIUM AND PLASTIC, ALL OF WHICH CONFORM TO EEC STANDARDS FOR FOOD GRADE MATERIALS
- A COMPETITIVE PRICE AND HIGH QUALITY FINAL RESULTS

THE MACHINE INCLUDES:

- 2 CUP DISPENSERS
- 2 FILLING NOZZLES
- 2 LID DISPENSERS
- 2 HEAT SEALING SYSTEMS
- 2 PHOTO ELECTRIC EYES TO CHECK LIDS' PRESENCE
- 2 CUP EJECTION SYSTEMS
- 2 CONTROL PANELS
- 2 ROTATING PLATFORMS 9 STATIONS FOR CUPS 100-200 CC (3.5-7 Oz)

OPTIONALS:

- ROTATING PLATFORM 7 STATIONS FOR CUPS 100-500 CC (3.5-20 Oz), DIAM. 95 mm (0.4 inch)
- LID DATE CODER
- SECOND FILLING NOZZLE
- ADDITIONAL NOZZLE FOR PASTES
- EXIT CONVEYOR

A TYPICAL AUTOMATIC PROCESS INCLUDES THE FOLLOWING OPERATIONS:

- CUPS INSERTED INTO SOLETS IN ROTATING PLATFORMS
- CUPS MOVED UNDER NOZZLES
- PRODUCT FILLED DIRECTLY FROM CUSTOMER'S CONTAINER
- PRE-PUNCHED ALUMINIUM-FOIL LIDS ON THE CUPS
- CODING PRINTED ON LIDS (OPTIONAL)
- CUPS EJECTED - CLEAN, DRY, READY FOR PACKING

TECHNICAL DATA

	EUROPEAN STANDARDS	USA STANDARDS
POWER SUPPLY	220 V, 50 Hz	220 V, 50-60 Hz 3 phase
CONTROL VOLTAGE	24 V	24 V
POWER INSTALLED	2 KW	2.5 H.P.
COMPRESSED AIR CONSUMPTION	500 L/min	130 Gal/min
AIR PRESSURE	6-8 Bar	90-120 p.s.i.
LENGTH	710 mm	28 inch
WIDTH	1300 mm	51 inch
HEIGHT	1400 mm	55 inch
NET WEIGHT	290 Kg	640 Lb
OUTPUT	60 pcs/min	60 PCS/min

NOTE:

1. "OPTION" OF "OPTIONAL" REFERS TO PARTS, SERVICES OR OPERATIONS ON SPECIAL ORDER AND AT ADDITIONAL COST.
2. IN KEEPING WITH PACK LINE'S POLICY OF ONGOING PRODUCT IMPROVEMENTS, THE DESIGNS AND SPECIFICATIONS IN THIS PUBLICATION ARE SUBJECT TO CHANGE WITHOUT NOTICE.



PACK LINE Ltd

Packaging Machines Industries